

PLAYGROUND SAFETY INSPECTION

General Hazards Worksheet

(Complete one worksheet for each Playground)

Yes	No	N/A	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	General Requirements (<i>ASTM F 1487-11, Section 5</i>) (<i>CPSC #325-10 Section 3</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Play equipment designed for a specific age group shall have all play activities on that equipment meet the requirements for that age group.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Play structures are anchored to the ground or not be intended to be relocated.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Designated Play Surfaces (<i>ASTM F 1487-11, Section 7.5.5 Section 7.5.6 Section 8.3.6 and Section 8.6.1.2</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Guardrails, Barriers, Equipment Support Posts and Swing Structures and do not have designated play surfaces.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Head and Neck Entrapment (<i>ASTM F 1487-11, Section 6.1</i>) (<i>CPSC #325-10 Section 3.3.1</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	All completely bounded openings are less than 3.5" or larger than 9" (<i>Openings that have the fall-surface as the lower boundaries are exempt.</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	All partially bound openings are in compliance (<i>ASTM F 1487-11, Section 6.1.4</i>) (<i>Partially bound openings less than 24 inches above the surface are exempt</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Depth of penetration issues comply with CPSC #325-10 Appendix B 2.5.4
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Non rigid climbing components comply with CPSC #325-10, Appendix B 2.5.5
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	All angles are greater than 55 degrees. (<i>CPSC #325-10, Section 3.3.2</i>) (<i>Angles that slope down or are horizontal are exempt.</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Sharp Points and Sharp Edges (<i>ASTM F 1487-11, Section 6.2</i>) (<i>CPSC #325-10 Section 3.4</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There shall be no sharp points or sharp edges on public play equipment
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The ends of all tubing shall be provided with caps or plugs that can not be removed.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Cut off bolts shall be free of burrs, sharp points and sharp edges.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Protrusions/Impalements (<i>ASTM F 1487-11, Section 6.3</i>) (<i>CPSC #325-10 Section 3.2</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	No protrusions extend beyond the face of any of the three test gauges shown in Fig. A 1.10
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Entanglements (<i>ASTM F 1487-11, Section 6.4</i>) (<i>CPSC #325-10 Section 3.2</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There are no entanglement hazards on play equipment
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Crush, and Shearing Points (<i>ASTM F 1487-11, Section 6.5</i>) (<i>CPSC #325-10 Section 3.1</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There are no accessible crush, or shearing points on playground equipment that could entrap a .62 dia. rod.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Suspended Hazards (<i>ASTM F 1487-11, Section 6.6</i>) (<i>CPSC #325-10 Section 3.5</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	No single cables, wires, ropes or similar flexible components are suspended between play units or from the ground to a unit within 45 degrees of horizontal unless it is above 84 inches high.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Single single cables, wires, ropes or similar flexible components are a minimum of 1" at its widest dimension.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The rope, cable or chain shall be fixed at both ends and not be capable of being looped back on itself, creating an inside loop perimeter greater than 5 inches.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The rope or cable is brightly colored or contrast with its surroundings.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Chains and cables used for swings are exempt.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Rope, cables and chain less than 7 inches long are exempt.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Ropes are not used to suspend swings.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Tripping Hazards (<i>CPSC # 325 Section 9.7</i>) (<i>CPSC #325-10 Section 3.6</i>)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	All anchoring devices, including horizontal bars and footings are below ground level.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There are no broken or raised sections of walkways
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There are no damaged (including separated vinyl) surfacing on the decks and ramps.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The Geotextile fabric under the Loose Fill surfacing is not exposed.

Maintenance Condition: Good, Needs repair

Priority: Priority 1 Priority 2 Priority 3 Compliant

Comments:
