

# PLAYGROUND SAFETY INSPECTION

## Slide Worksheet

(Complete one worksheet per Slide)

**Slides with one turn (360 deg.) or less are recommended**

**Type of slide:**     Straight     Curved     Spiral     Roller     Tube

**Height of Slide:** \_\_\_\_\_    **Description**    \_\_\_\_\_

<b>Yes</b>	<b>No</b>	<b>N/A</b>	<b>General</b> (ASTM F 2373-11 Section 9.3) (CPSC #325-10 Section 5.3.6)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Soft foam play structures are exempt from the requirements for slides.

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Platform</b>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Minimum length is 19" or greater
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Width is equal to or wider than width of slide
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Handholds are on both sides of slide
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The slide entry channels the user into a sitting position (guardrail, hood etc.)

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Slide</b>
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The average incline of a slide chute does not exceed 0.445 (24 deg.)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	No section of the slide chute should have a slope greater than 30 deg.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The side rail on flat slides is a min. of 4" high for full length of the slide
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The slide chute width is no less than 8" or more than 12"

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Exit region</b>	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If the slide slope exceeds 24 deg. the slide has an exit region with a minimum length of 7" and a maximum of 10"	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The slope is between 0 and - 4 deg.	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Slide exit height is no more than 6"	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Exit region is rounded or curved	

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Use Zone</b> (ASTM F 2373-11 Section 11.5)	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	In indoor and outdoor supervised settings the use zone is 36' from all portions of structure	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	In settings with unlimited access the use zone is 72' from all portions of structure	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The use zone of no other equipment overlaps the exit zone of the slide	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The use zones of all slides have impact attenuation surfaces.	

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Slide Exit Clearance Zone</b> (ASTM F 2373-11 Section 9.3.6)	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Slide clearance zone extends to the end of the use zone	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Side clearance is 18 " horizontal from inside face of side wall at top of sidewalls	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Side clearance zones of parallel slides may overlap	Actual _____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	34' vertical from slide surface.	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Clearance zones of merging slides do not overlap	

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<b>Slide Entanglement Zone</b> (ASTM F 2373-11 Section 6.4.1) (CPSC #325-10 Appendix B 2.3)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The slide is free of entanglement hazards

**Maintenance Condition:**     Good     Needs repair

**Priority:**     Priority 1     Priority 2     Priority 3     Compliant

**Comments:** \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_