

# PLAYGROUND SAFETY INSPECTION

## Sliding Poles Worksheet

(Complete one worksheet for each Pole)

**Intended age of user:**  2 to 5 year old  5 to 12 year old  2 to 12 year old  
 Free Standing Pole height minus 60" \_\_\_\_\_  Deck Access Deck Ht: \_\_\_\_\_

Yes	No	N/A	General (ASTM F 1487-11 Section 8.4) (CPSC #325-10 Section 5.3.2.6)	Actual
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Sliding poles are not recommended for 2 to 5 year old users.	_____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Clearance from pole to structure is between 18" and 20"	_____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The pole is a minimum of 60" above access deck height	_____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	There is access from one deck only	_____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The pole is less than 1.9" diameter	_____
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	The opening in the guardrail or protective barrier is less than 15"	_____

### Guardrails and Barrier Panels

(ASTM F 1487-11 Section 7.5.5) (CPSC #325-10 Section 5.1.3)

#### 2-5 year old users

Guardrails (20 to 30 inch decks)  
   Barrier Panels (30 inch + decks) or all decks

#### 5-12 year old users

Guardrails (30 to 48 inch decks)  
   Barrier Panels (48 inch + decks) or all decks

#### Use Zone (ASTM F 1487-11 Section 9.3.2) (CPSC #325-10 Section 5.3.2.1.4)

Minimum 72" in all directions from the perimeter of the unit  
   Minimum 72" between adjacent structures that are under 30"  
   Minimum 108" between adjacent structures if one of them is more than 30" high  
   Part of a composite structure

**Maintenance Condition:**  Good,  Needs repair  
**Priority:**  Priority 1  Priority 2  Priority 3  Compliant

**Comments:**

---

---

---

---

---

---

---

---

---

---